



DESCRIPTION

- AMARSIS ADDITIVE is an acrylic emulsion based, metallic silver and gold finish, auxiliary product added in AMARSIS at a certain rate.

APPLICATION AREA

- It is added in AMARSIS and applied to interior wall surfaces where surface preparation is completed.

SURFACE PREPARATION

- After all kinds of dirt, oil, blistered paint and dust are cleaned from the surfaces of application, the surface defects should be smoothened with SAN DECO ACRYLIC PUTTY INTERIOR, if any.

FEATURES

- It brings gold and silver reflection to AMARSIS in which it is added.
- It does not harm human health and environment as it is water-based.

The Product

Composition	Acrylic Based
Density	1,03 g/cm ³
	8,59 lbs./gallon
Storage Temperature	5 °C + 35 °C 41 °F + 95 °F
Emission Limits of Volatile Organic Compounds (VOC) According to Directive 2004/42/CE	Subcategory: G VOC: 12 g/l (max); Limit Phase : 200 g/l
Weight Per Gallon	8,59 lbs.
Packaging	1 Pint
Dilution	Ready To Use

APPLICATION INSTRUCTION

- Standard application of AMARSIS is undertaken with AMARSIS ADDITIVE added 10% in AMARSIS by being mixed homogenously.

THEORETICAL CONSUMPTION

- 250 ml of AMARSIS ADDITIVE is added in 2,5 liters of AMARSIS.

STORAGE

- It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C and +35°C.



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: Please refer to the product's Safety Data Sheet (SDS) for more information.

Product Technical Data Sheet No. DP. 013.US - Rev01 January 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 27001, ISO 45001.

SAN DECO

Paint Manufacturing & Distribution

Headquarters: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul

Contact: +1 786-224-14-64