


ACRYLIC BASED, FLAKE ADDED DECORATIVE PAINT



DESCRIPTION

GALAXY is an acrylic emulsion based, flake added, ready-to-use decorative paint.

Thanks to its appearance, it creates modern and stylish spaces where you will enjoy elegance.

APPLICATION AREA

Adding depth and character to all kinds of interior walls, GALAXY is used together with the appropriate primer on walls, plaster, gross concrete and wooden surfaces after surface preparation.

SURFACE PREPARATION

After all kinds of dirt, oil, blistered paint and dust are cleaned from the surfaces of application, the surface defects should be smoothed with SAN DECO ACRYLIC PUTTY INTERIOR. Already-painted and dirty surfaces should be primed with SAN DECO DECOPRIMER.

DECOPRIMER should be diluted with 20-25% of clean water by volume and applied 2 layers on the surface with a brush or roller; complete drying should be ensured between the layers.

FEATURES

- It is a decorative material for indoors.
- It creates an extraordinary old wall affect due to its special, granular structure.
- Thanks to its transparent film characteristics, it does not change the color of the surface on which it is applied.
- It does not harm human health and environment as it is water-based.
- It causes environments to smell nice due to its perfume characteristic.

The Product

Composition	Acrylic Based
Density	1.03 g/cm ³
	8.59 lbs./gallon
Storage Temperature	5 °C ÷ 35 °C 41 °F ÷ 95 °F
Emission Limits of Volatile Organic Compounds (VOC) According to Directive 2004/42/CE	Subcategory: K VOC: 26 g/l (max); Limit Phase : 100 g/l
Theoretical Coverage (Single Coat)	265 – 326 sq. Ft/gallon
	6,5 – 8,0 m ² /L
Weight Per Gallon	8,59 lbs.
Packaging	1 Gallon

The Application

Dilution	Ready To Use
Surface Preparation	San Deco Acrylic Putty Interior
Primer	San Deco Decoprimer
Application Tools	Brush, Plastic Spatula
Touch Dry Time	4-5 Hours
Complete Dry Time	24-48 Hours
Dry Time Temperature	23 °C - 73.4°F (relative humidity at 50%)
Application Temperature (24 hours during and after the application)	5 °C ÷ 35 °C 41 °F ÷ 95 °F

SAN DECO

Paint Manufacturing & Distribution

Headquarters: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul

Contact: +1 786-224-14-64

APPLICATION INSTRUCTION

- After the primer dries, GALAXY is carefully mixed with a spatula and applied to the surface with its special wooden brush. After 25 minutes, the final appearance is achieved by tilting on the surface with a plastic spatula. Depending on application techniques, different decorative effects can be acquired.
- It should be paid attention that the ambient temperature should be minimum +5°C/41 °F, and maximum +35°C/95 °F within 24 hours during and after the application.

DRYING TIME

At 23°C/73.4°F, the touching time is 4-5 hours and the complete drying time is 24-48 hours.

THEORETICAL CONSUMPTION

For one-layer application, depending on the surface smoothness, absorbency and application techniques;

-6,5 - 8,0 m² with 1 lt.

-6,0 - 7,5 m² area is painted with 1 kg.

- Paint consumption for an area of 1 m² is 125 - 150 ml and 130 - 165 gr.

STORAGE

It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C/41 °F and +35°C/95 °F.



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP. 009.US - Rev01 January 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 27001, ISO 45001.